

Just where you need it.



Products you need
from people who care



NTI COMPACT

Mini-tank electric water heaters

The NTI COMPACT mini-tank electric water heaters are the ideal choice to provide hot water to stand-alone faucets or to eliminate waiting time and increase capacity of existing systems. Its elegant and compact design ensures it will be able to fit any application and allows flexible wall hung or floor mounted installation. It could not be easier: simply place it, plug in the factory supplied electric connection, connect the piping and enjoy hot water, just where you need it.

Ideal for:

- Half bathrooms and isolated sinks
- Industrial locations such as warehouses and factories
- Bar, store and office bathrooms
- Ancillary rooms in restaurants and hotels
- Remote houses, mobile homes and boats





Get it done in a snap

- Easy one-person installation
- Plugs into standard wall outlets
- Mounting bracket included
- NTI COMPACT 6 can be installed horizontally or vertically

Three sizes available
from 2.7 gal to 7 gal



Pictures are for illustrative purposes only.
For more information, please refer to Installation Manual.



POINT-OF-USE

- Single faucets
- Remote locations
- Single water lines

BOOSTER

- No waiting time
- Eliminates cold water sandwich
- No minimum flow rate requirement





6y / 1y
TANK / PARTS
WARRANTY

4
BOLTS
FLANGE

Ti
GLASS
LINED TANK

Mg
SACRIFICIAL
ANODE


HIGH ACCURACY
THERMOSTAT

MODEL	NTI COMPACT 2.5	NTI COMPACT 4	NTI COMPACT 6
Tank capacity	2.7 gal	4.0 gal	7.0 gal *
Dimensions	13 3/4" W x 13 3/4" H x 10 3/4" D	13 3/4" W x 13 3/4" H x 13 1/2" D	17 3/5" W x 17 3/5" H x 14 1/2" D
Weight (empty)	15.5 lbs	17.3 lbs	29.5 lbs
Maximum Water pressure	150 psi	150 psi	150 psi
Recovery rate at 90°F rise	6.8 gal/h	6.8 gal/h	6.8 gal/h
Temperature range	65 – 145 °F	65 – 145 °F	65 – 145 °F
Water connections	1/2" NPT	1/2" NPT	3/4" NPT
Relief valve	Installed	Installed	Included
Nominal voltage (1 phase)	110/120 Vac	110/120 Vac	110/120 Vac
Nominal current	12 A	12 A	12 A
Power at 120 Vac	1,440 W	1,440 W	1,440 W
Electrical Connection	Plug-in	Plug-in	Hard wired
Sizing			 

* 5.1 gal if installed vertically



30 Stonegate Drive, Saint John
New Brunswick, Canada, E2H 0A4
Tel. +1 506 657 6000
Toll-free: 800 688 2575
Fax: +1 506 432 1135
ntiboilers.com

For more information:
Contact your local NTI representative or visit ntiboilers.com